

Specification of Tsudakoma Air-Jet รายละเอียดประกอบกรจำหน่ายทรัพย์สิน ครั้งที่ 13 ชุดที่ 1 ลำดับ 1

Item	Description	ZAX
1	General Manufacturing date (MFD.) Reed space : 190 cm.	24 set 2001 190 cm.
2	Frame :	MAX.6 HEALD FRAMES
3	Driving : 3-1 Power supply : Suitable for 380 V, 50 Hz, 3 ph., 4 wire system 3-2 Provided with : One set of rush start motor 3.7 Kw, 4 p	
4	Shedding : Cam shedding Plain Weave 1/1 Twill 2/1 Twill 2/2 Twill 3/1	staubli 1620B 2 14 4 4
5	Let-off : Warp beam, flanges and warp beam gear. (1.5 Beam/MC)	36
6	Take-up : Provided with : One pc. of standard gear : One pc. of pick change gear : One set of temple (L&R) Cloth roller	1.5 Roller/MC
7	Beating : Profile reed	1 Reed/MC
8	Weft selection : 2 color mixing (1 x 1.9 x 9)	2 color mixing
9	Selvage formation : Intertwisting system by planetary gear motion. With 4 pcs. of leno bobbin	
10	Waste weft removal : By catch cord system on right side only	
11	Cutter : Mechanical cutter, scissors type	
12	Lubrication : Oil bath system built in the main frame for main revolution parts With centralized lubrication system by manual pump	
13	Weft supply stand : Horizontal type for 2 packages	
14	Control box : Power controller by magnetic contactors. Unit built-in system, function controlled by printed circuit boards micro-processors	
15	Stop motion : With signal lamp of 4 colour system for indicating each stop cause Warp stop motion : Electric warp stop motion, 6 banks.(6 pcs. of dropper bar) Weft feeler : Photo-electronic 2 head feelers, fabric width adjustable type Leno yarn : Electric system with proximity switch Catch cord yarn : Electric dropper system Dropper pin	
16	i-Board i-Board with data setting,automatic control ,self diagnosis function with auto computer With auto counter function (meter, yard or pick)	
17	AJC With Auto Jet Controller (AJC) for analyzing filling arrival timing and controlling FDP.	
18	Inverter	2 SET
19	SPEED 650 - 750 RPM.	

Included

Item	Description	Quantity
1	Flat Steel Headle (Type J,Simplex)	133,891
2	Drop Wire	133,891
3	Heald Frames	104