

Specification of Tsudakoma Air-Jet รายละเอียดประกอบการจำหน่ายทรัพย์สิน ครั้งที่ 13 ชุดที่ 2 ลำดับ 1

Item	Description	ZAX-e
1	General Manufacturing date (MFD.) Reed space : 190 cm.	48 set 2003 190 cm.
2	Frame :	MAX.7 HEALD FRAMES
3	Driving : 3-1 Power supply : Suitable for 380 V, 50 Hz, 3 ph., 4 wire system 3-2 Provided with : One set of rush start motor 3.7 Kw, 4 p	
4	Shedding : Cam shedding Twill 2/1 Twill 2/2 Twill 3/1 Satin 4/1	staubli 1661 18 11 1 18
5	Take-up : Provided with : One pc. of standard gear : One pc. of pick change gear : One set of temple (L&R) Cloth roller	1.5 Roller/MC
6	Beating : Profile reed	1 Reed/MC
7	Weft selection : 2 color mixing (1 x 1.9 x 9)	2 color mixing
8	Selvage formation : Intertwisting system by planetary gear motion. With 4 pcs. of leno bobbin	
9	Waste weft removal : By catch cord system on right side only	
10	Cutter : Mechanical cutter, scissors type	
11	Lubrication : Oil bath system built in the main frame for main revolution parts With centralized lubrication system by manual pump	
12	Weft supply stand : Horizontal type for 2 packages	
13	Control box : Power controller by magnetic contactors. Unit built-in system, function controlled by printed circuit boards micro-processors	
14	Stop motion : With signal lamp of 4 colour system for indicating each stop cause Warp stop motion : Electric warp stop motion, 6 banks.(6 pcs. of dropper bar) Weft feeler : Photo-electronic 2 head feelers, fabric width adjustable type Leno yarn : Electric system with proximity switch Catch cord yarn : Electric dropper system Dropper pin	
15	i-Board i-Board with data setting,automatic control ,self diagnosis function with auto computer With auto counter function (meter, yard or pick)	
16	AJC With Auto Jet Controller (AJC) for analyzing filling arrival timing and controlling FDP	
17	Inverter	2 SET
18	Speed 650 - 750 RPM	

Included

Item	Description	Quantity
1	Flat Steel Headle (Type J,Simplex)	322,767
2	Drop Wire	322,767
3	Heald Frames	250